

Specifications

These rod magnets are 0.125 inch (3.2mm) diameter and 1.000 inch (25.4mm) long. They are magnetized through the length. They are composed of grade 40 neodymium iron boron magnetic material and are plated in nickel-copper-nickel for a shiny corrosion resistant finish. Their individual pull force is approximately 4 lbs. Maximum working temperature is 176 F (80 C).



Part Number	NSN0750
Imperial Dimensions	0.125 inch diameter x 1 inch long
Metric Dimensions	3.175mm diameter x 25.4mm long
Material	Sintered Neodymium-Iron-Boron (NdFeB)
Shape	Rod
Plating	Ni-Cu-Ni (Nickel)
Magnetization Direction	Length
Grade	N40
Pull Force	4.05[1837]
Surface Field	4408
Packaging	Magpak Tube
UPC	875661001501
Magnet Quantity	14
Brand	Magcraft

Maximum Operating Temperature	80 Deg C (176 Deg F)
Maximum Energy Product Bhmax (MGOe (kJ/m ³))	38-41 [302-326]
Remanent Flux Density Br (kG (T))	12.5-12.8 [1.25-1.28]
Coercivity HcB (kOe (kA/m))	≥11.3 [≥923]
Intrinsic Coercivity HcJ (kOe (kA/m))	≥12.0 [≥995]
Dimensional Tolerance	+/-0.005"
Density ρ (g/cm ³)	≥7.45
Compression Strength (Mpa)	600-1200
Bending Strength (Mpa)	150-380
Vickers Hardness (HV)	460-660
Recoil Permeability (μrec)	1.05
Electrical Resistance (Ω·mm ² /m)	1.25-1.55
Curie Temperature Tc (°C)	310
Thermal Expansion Coefficient 100°C // (x10 ⁻⁶ /K)	6
Thermal Expansion Coefficient 100°C ⊥ (x10 ⁻⁶ /K)	-1

