

Specifications

These rod magnets are 0.250 inch (6.4mm) diameter and 1.000 inch (25.4mm) long. They are magnetized through the length. They are composed of grade 40 neodymium iron boron magnetic material and are plated in nickel-copper-nickel for a shiny corrosion resistant finish. Their individual pull force is approximately 10 lbs. Maximum working temperature is 176 F (80 C).



Part Number	NSN0719
Imperial Dimensions	0.25 inch diameter x 1 inch long
Metric Dimensions	6.35mm diameter x 25.4mm long
Material	Sintered Neodymium-Iron-Boron (NdFeB)
Shape	Rod
Plating	Ni-Cu-Ni (Nickel)
Magnetization Direction	Length
Grade	N40
Pull Force	10.68[4844]
Surface Field	5219
Packaging	Magpak Tube
UPC	875661000191
Magnet Quantity	6
Brand	Magcraft
Maximum Operating Temperature	80 Deg C (176 Deg F)
Maximum Energy Product Bhmax (MGOe (kJ/m3))	38-41 [302-326]
Remanent Flux Density Br (kG (T))	12.5-12.8 [1.25-1.28]
Coercivity HcB (kOe (kA/m))	≥11.3 [≥923]
Intrinsic Coercivity Hcj (kOe (kA/m))	≥12.0 [≥995]
Dimensional Tolerance	+/-0.005"
Density ρ (g/cm3)	≥7.45
Compression Strength (Mpa)	600-1200
Bending Strength (Mpa)	150-380
Vickers Hardness (HV)	460-660
Recoil Permeability (μrec)	1.05
Electrical Resistance (Ω·mm2/m)	1.25-1.55
Curie Temperature Tc (°C)	310
Thermal Expansion Coefficient 100°C // (x10 ⁻⁶ /K)	6
Thermal Expansion Coefficient 100°C ⊥ (x10 ⁻⁶ /K)	-1

